NSN 5930-00-296-9359

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-9359

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Fungus proof
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
0.937 inches
Overall Width:
0.281 inches
Body Length:
1.203 inches
Body Width:
0.281 inches
Body Height:
0.828 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.094 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.625 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Height:
0.109 inches
Actuator Free Position Height:
0.219 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:

20.0 grams

NSN 5930-00-296-9359

Sensitive Switch - Page 2 of 2



Switch Actuating Force	e:
------------------------	----

Between 45.0 grams and 60.0 grams

Actuator Movement:

0.040 pretravel inches and 0.050 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 3.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0