## NSN 5930-00-296-9368

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-296-9368

Case Material:  Metal  Maximum Voltage Rating In Volts: 230.0 ac and 250.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel  Nonpile-up Contact Arrangement:	
Metal  Maximum Voltage Rating In Volts: 230.0 ac and 250.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Panel  Nonpile-up Contact Arrangement:	
Maximum Voltage Rating In Volts: 230.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Nonpile-up Contact Arrangement:	
230.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Nonpile-up Contact Arrangement:	
Inclosure Type: Fully enclosed Mounting Method: Panel Nonpile-up Contact Arrangement:	
Fully enclosed  Mounting Method:  Panel  Nonpile-up Contact Arrangement:	
Mounting Method: Panel Nonpile-up Contact Arrangement:	
Panel Nonpile-up Contact Arrangement:	
Nonpile-up Contact Arrangement:	
1 two circuit, double break/double make, both positions maintained single	switch unit
Switch Actuating Force:	
8.0 ounces	
Contact Load Current Rating At Maximum Rated Voltage:	
150.000 milliamperes resistive dc and 10.000 amperes resistive ac	
Terminal Type And Quantity:	
4 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A053a0	