

View Online at <https://aerobasegroup.com/nsn/5930-00-296-9533>

Inside Diameter:

0.125 inches all connections

Overall Length:

4.562 inches

Overall Height:

2.188 inches

Overall Width:

2.906 inches

Body Length:

3.188 inches

Longest Horizontal Distance Between Mounting Centers:

0.812 inches

Longest Vertical Distance Between Mounting Centers:

1.062 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between 65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Base

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

27 all pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

250.0 milliamperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

21.00 actuation point pounds per square inch and 20.00 deactuation point pounds per square inch and 1.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Special Features:

Two no. 10-32 thd mtg studs 1.700 in. C to c

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0