# NSN 5930-00-296-9805

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-9805

Body S	tyle:
--------	-------

Hole mounted

#### Hazardous Locations/environmental Protection:

Driptight

# **Overall Length:**

1.469 inches

#### **Overall Height:**

1.875 inches

#### **Overall Width:**

0.500 inches

#### **Body Length:**

1.094 inches

#### **Body Width:**

0.500 inches

## Body Height:

1.875 inches

# Case Material:

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.138 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches

#### Actuator Style:

Round

#### Actuator Diameter:

0.250 inches

#### Actuator Height:

0.375 inches

#### **Actuator Free Position Height:**

0.375 inches

#### Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Threaded hole

## Thready Qty Per Inch (tpi):

32

# Thread Size:

0.138 inches

# Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

# NSN 5930-00-296-9805

Sensitive Switch - Page 2 of 2



Switch Release Force:

4.0 inch-ounces

Switch Actuating Force:

6.0 inch-ounces

**Actuator Movement:** 

0.172 pretravel inches and 0.437 overtravel inches and 0.096 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes inductive dc and 10.000 amperes resistive ac

**Thread Series Designator:** 

Unc

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0