

View Online at <https://aerobasegroup.com/nsn/5930-00-300-1701>

Overall Length:

10.312 inches

Unthreaded Mounting Hole Diameter:

0.525 inches single mounting facility

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

5.625 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.625 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

4 each section front

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

450.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Criticality Code Justification:

Zzzy

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section front

Contact Load Current Rating:

200.0 amperes resistive load dc at sea level

Special Features:

Auxiliary mounting method, rear support bracket, two unc 1/4-20 threaded mounting holes, 3-13/16 inches distance between mounting hole centers

Style Designator:

Tap, circuit selector

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0