

View Online at <https://aerobasegroup.com/nsn/5930-00-300-1947>

Thread Length:

0.360 inches single mounting facility and 0.390 inches single mounting facility

Overall Length:

1.862 inches

First Flat Length:

0.460 inches single actuator and 0.490 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.253 inches single actuator

Shaft Length:

0.985 inches single actuator and 1.015 inches single actuator

Overall Diameter:

1.015 inches

Nonturn Device Radius:

0.375 inches at 1:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 1:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 ac at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0