

View Online at <https://aerobasegroup.com/nsn/5930-00-306-0182>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Height:**

5.875 inches

**Overall Width:**

6.625 inches

**Shaft Diameter:**

0.312 inches single actuator

**Shaft Length:**

0.438 inches single actuator

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

04009

**Longest Horizontal Distance Between Mounting Centers:**

3.625 inches single mounting facility

**End Application:**

Bnimitz class cvn, forrestal class cv, oliver perry class ffg, seawolf class ssn, virginia class cgn (41), tarawa class lha, sturgeon class ssn (637), los angeles class ssn (688), wasp class lhd.

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 single section front

**Throw Quantity:**

1 single section front

**Mounting Method:**

Base single mounting facility

**Features Provided:**

Actuator knob and metallic inclosure

**Contact Voltage Rating In Volts:**

115.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Positioning Increment:**

105.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

**Special Features:**

Weapon system essential

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0