

View Online at <https://aerobasegroup.com/nsn/5930-00-306-0182>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Height:

5.875 inches

Overall Width:

6.625 inches

Shaft Diameter:

0.312 inches single actuator

Shaft Length:

0.438 inches single actuator

Individual Section Quantity:

1

Knob Manufacturer Code:

04009

Longest Horizontal Distance Between Mounting Centers:

3.625 inches single mounting facility

End Application:

Bnimitz class cvn, forrestal class cv, oliver perry class ffg, seawolf class ssn, virginia class cgn (41), tarawa class lha, sturgeon class ssn (637), los angeles class ssn (688), wasp class lhd.

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

1 single section front

Mounting Method:

Base single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

115.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

105.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Special Features:

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0