NSN 5930-00-306-0670

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-306-0670

| Hazardous Locations/environmental Protection: |
|--|
| Dustproof |
| Overall Height: |
| 2.188 inches |
| Overall Width: |
| 2.750 inches |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 1.750 inches single actuator |
| Individual Section Quantity: |
| 2 |
| Knob Manufacturer Code: |
| 04009 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Throw Quantity: |
| 2 each section front |
| Mounting Facility Circle Radius: |
| 1.156 inches single mounting facility |
| Features Provided: |
| Actuator knob |
| Thready Qty Per Inch (tpi): |
| 24 single mounting facility |
| Thread Size: |
| 0.190 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 250.0 ac at sea level |
| Switch Actuator Momentary Position: |
| Clockwise single actuator and counterclockwise single actuator |
| Mounting Facility Pattern: |
| Four position circular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 4 single actuator |
| Shaft Type: |
| Round single actuator |
| Terminal Type: |
| Tab w/screw |

Contact Switching Action:

Breaks before makes each section front

NSN 5930-00-306-0670

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0