NSN 5930-00-307-4130

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-307-4130

| Overall Length: | |
|---|--|
| 10.000 inches | |
| Overall Height: | |
| 6.750 inches | |
| Overall Width: | |
| 6.750 inches | |
| Unthreaded Mounting Hole Diameter: | |
| 0.531 inches single mounting facility | |
| Individual Section Quantity: | |
| 3 | |
| Knob Manufacturer Code: | |
| 82121 | |
| Knob Manufacturer Part Number: | |
| A | |
| Longest Horizontal Distance Between Mounting Centers: | |
| 5.625 inches single mounting facility | |
| Longest Vertical Distance Between Mounting Centers: | |
| 5.625 inches single mounting facility | |
| Switch Contact Basic Design: | |
| Nonpile-up symmetrical | |
| Pole Quantity: | |
| 1 each section front | |
| Throw Quantity: | |
| 4 each section rear | |
| Features Provided: | |
| Actuator knob | |
| Contact Voltage Rating In Volts: | |
| 600.0 ac at sea level | |
| Rotor Through Connection Quantity: | |
| 1 each section | |
| Mounting Facility Pattern: | |
| Four position rectangular single mounting facility | |
| Switch Actuator Indexing Position Quantity: | |
| 4 single actuator | |
| Contact Switching Action: | |
| Breaks before makes each section rear | |
| Switch Actuator Positioning Increment: | |
| 90.0 degrees single actuator | |
| Contact Load Current Rating: | |
| 200.0 amperes resistive load ac at sea level | |
| Style Designator: | |
| | |

Tap, circuit selector

NSN 5930-00-307-4130

Rotary Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

