## NSN 5930-00-308-4240

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-308-4240

**Thread Class:** 

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

**Overall Length:** 

2.188 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.688 inches single actuator

**Overall Diameter:** 

1.875 inches

**Nonturn Device Radius:** 

0.531 inches at 10: 30 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Tab at 10: 30 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section rear

**Throw Quantity:** 

8 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

110.0 ac at sea level

**Switch Actuator Indexing Position Quantity:** 

8 single actuator

**Shaft Type:** 

Round single actuator

Terminal Type:

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-308-4240

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.0 amperes resistive load ac at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0