## NSN 5930-00-308-4257

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-308-4257

**Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 2.250 inches **Overall Height:** 1.875 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.250 inches single actuator **Nonturn Device Radius:** 0.531 inches at 9: 00 o'clock **Individual Section Quantity:** 2 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 6 each section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Metallic inclosure **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** 

Breaks before makes each section rear

## NSN 5930-00-308-4257

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 1.0 amperes resistive load ac at sea level **Precious Material And Location:** Contacts and rotor blades silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure:**

**Demilitarization:** 

No Fiig: A052b0