# NSN 5930-00-308-4270

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-308-4270

#### **Thread Class:**

2a single mounting facility

#### Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

2.375 inches

#### **Overall Height:**

1.875 inches

#### **Overall Width:**

1.516 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.625 inches single actuator

## Individual Section Quantity:

2

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

2 each section rear

#### Throw Quantity:

4 each section rear

#### Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

4 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

0.5 amperes resistive load ac at sea level

# NSN 5930-00-308-4270

Rotary Switch - Page 2 of 2



**Precious Material And Location:** Contacts silver and rotor blade silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0