# NSN 5930-00-308-4271

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-308-4271

#### **Thread Class:**

2a single mounting facility

#### Thread Length:

0.375 inches single mounting facility

### **Overall Length:**

1.750 inches

#### **Overall Height:**

1.875 inches

#### **Overall Width:**

1.516 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.625 inches single actuator

#### Individual Section Quantity:

1

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 single section rear

## Throw Quantity:

3 single section rear

#### Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes single section rear

#### Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

### **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

# NSN 5930-00-308-4271

Rotary Switch - Page 2 of 2



**Precious Material And Location:** Contacts silver and rotor blade silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0