

View Online at <https://aerobasegroup.com/nsn/5930-00-309-4474>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.243 inches and 0.248 inches

Actuator Height:

Between 0.849 inches and 0.869 inches

Housing Height:

Between 1.094 inches and 1.156 inches

Housing Length:

Between 2.791 inches and 2.843 inches

Housing Width:

Between 1.095 inches and 1.155 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 2.432 inches and 2.442 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

Between 1.870 inches and 1.880 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

192.0 ounces

Actuator Movement:

Between 118.0 pretravel degrees and 100.0 overtravel degrees and 10.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 5.000 amperes inductive dc

Special Features:

Actuator on left hand side

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0