## NSN 5930-00-312-4115

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-312-4115
Thread Class:
2b all threaded hole
Inside Diameter:
0.250 inches single connection
Overall Length:
2.650 inches
Overall Height:
2.640 inches
Overall Width:
0.920 inches
Body Height:
2.640 inches
Distance Between Mounting Facility Centers:
0.688 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and threaded hole
Features Provided:
Capillary tube end seal connection
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Sensing Element Burst Pressure:
800.00 pounds per square inch
Terminal Type:

Screw

#### **Contact Load Current Rating:**

8.0 amperes resistive load single voltage and 48.0 amperes motor load single voltage

#### **Contact Adjustability:**

Deactuation point not adjustable, manual reset and actuation point not adjustable

#### **Contact Stimulus Rating:**

25.00 actuation point pounds per square inch gage

### **Contact Voltage Rating In Volts:**

240.0 ac at sea level single voltage

# NSN 5930-00-312-4115

Pressure Switch - Page 2 of 2

**Fiig:** A048b0



Pressure Connector Type:
Swivel nut with compression sleeve, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Unc all threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No