

View Online at <https://aerobasegroup.com/nsn/5930-00-313-1847>

Thread Class:

3b single pressure connection

Overall Length:

4.250 inches

Overall Width:

3.625 inches

Body Diameter:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

500.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.10/+30.00 actuation point pounds per square inch and +0.10/+30.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

6.00 actuation point pounds per square inch and 28.00 deactuation point pounds per square inch and 22.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0