## NSN 5930-00-313-2196

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-313-2196

## **Hazardous Locations/environmental Protection:**

Dustproof

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

1.156 inches single actuator

**Individual Section Quantity:** 

5

**Knob Specificationial Markings:** 

Arrow

**Longest Horizontal Distance Between Mounting Centers:** 

2.312 inches single mounting facility

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section rear

**Mounting Method:** 

Bracket single mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

115.0 ac at sea level

**Mounting Facility Pattern:** 

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

Shaft Type:

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

**Contact Load Current Rating:** 

10.0 amperes resistive load ac at sea level

**Thread Series Designator:** 

Unc single mounting facility

## NSN 5930-00-313-2196

Rotary Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0