NSN 5930-00-313-2196

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-313-2196

Hazardous Locations/environmental Protection:

Dustproof

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.156 inches single actuator

Individual Section Quantity:

5

Knob Specificationial Markings:

Arrow

Longest Horizontal Distance Between Mounting Centers:

2.312 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Thread Series Designator:

Unc single mounting facility

NSN 5930-00-313-2196

Rotary Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0