

View Online at <https://aerobasegroup.com/nsn/5930-00-314-0367>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.563 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.313 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.217 inches single actuator

**Shaft Diameter:**

0.314 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Overall Diameter:**

1.500 inches

**Nonturn Device Radius:**

0.625 inches at 12: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.500 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Connector, plug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0