

View Online at <https://aerobasegroup.com/nsn/5930-00-314-0367>

Thread Class:

2a single mounting facility

Thread Length:

0.563 inches single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.313 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.217 inches single actuator

Shaft Diameter:

0.314 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

1.500 inches

Nonturn Device Radius:

0.625 inches at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.500 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Connector, plug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0