NSN 5930-00-315-0403



Push-pull Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-315-0403 **Thread Class:** 2b **Body Style:** Hole mount **Hazardous Locations/environmental Protection:** Dustproof **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.190 inches **Body Length:** 4.500 inches **Body Width:** 0.880 inches **Body Height:** 1.980 inches **Actuator Length:** 1.980 inches **Actuator Style:** Rectangular **Actuator Height:** 1.437 inches **Actuator Width:** 0.880 inches **Actuator Inscription:** Push to test single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Features Provided:** Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Nonpile-up Contact Arrangement:

8 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes motor dc and 5.000 amperes resistive ac

Thread Series Designator:

Unc

NSN 5930-00-315-0403Push-pull Switch - Page 2 of 2



reminal Type And Quantity:
24 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0