NSN 5930-00-316-2728

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-316-2728

view Online at https://aerobasegroup.com/nsn/5930
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.719 inches
First Flat Length:
0.500 inches single actuator
Flat Height:
0.311 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.688 inches single actuator
Unthreaded Mounting Hole Diameter:
0.234 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
04009
Knob Manufacturer Part Number:
10931-n1
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
1 each section front
Mounting Facility Circle Radius:
2.312 inches single mounting facility
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
450.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:

Threaded stud

NSN 5930-00-316-2728

Rotary Switch - Page 2 of 2



Con	tact	Swit	chino	ı Acti	on:
OUL	ıavı	OWIL	CHILL	ı Actı	vii.

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0