## NSN 5930-00-316-9124

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-316-9124

Thread Le	ngth:
-----------	-------

0.375 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

3.188 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

2.375 inches single actuator

**Overall Diameter:** 

1.250 inches

**Individual Section Quantity:** 

1

## **Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:** 

2 single section rear

**Throw Quantity:** 

5 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Metallic inclosure

Thread Size:

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

6.0 lowest dc voltage rating at sea level

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## **Contact Load Current Rating:**

200.0 milliamperes resistive load ac at sea level and 5.0 amperes resistive load ac at sea level

## NSN 5930-00-316-9124

Rotary Switch - Page 2 of 2



Style	De	sia	nato	١r٠
OLYIC	De.	oıg:	IIau	<i>,</i> ,

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0