

View Online at <https://aerobasegroup.com/nsn/5930-00-320-6722>

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

0.431 inches

**Shaft Diameter:**

0.168 inches single actuator

**Shaft Length:**

0.028 inches single actuator

**Overall Diameter:**

0.364 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

7 single section rear

**Mounting Method:**

Printed circuit single mounting facility

**Contact Voltage Rating In Volts:**

5.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from contact position 1 single actuator

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, slotted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Detent Rotational Torque Range:**

+2.000/+4.000 inch-ounces single actuator

**Contact Load Current Rating:**

100.0 milliamperes resistive load dc at sea level

**Style Designator:**

Miniature, pin mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0