NSN 5930-00-321-0255

Liquid Level Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-321-0255

Overall Length: 4.000 inches Power Cable Length: 56.000 inches Overall Height: 3.375 inches Overall Width: 1.250 inches Dc Voltage Rating: 28.0 volts Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
Power Cable Length: 56.000 inches Overall Height: 3.375 inches Overall Width: 1.250 inches Dc Voltage Rating: 28.0 volts Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
56.000 inches Overall Height: 3.375 inches Overall Width: 1.250 inches Dc Voltage Rating: 28.0 volts Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
Overall Height: 3.375 inches Overall Width: 1.250 inches Dc Voltage Rating: 28.0 volts Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
3.375 inches Overall Width: 1.250 inches Dc Voltage Rating: 28.0 volts Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
Overall Width: 1.250 inches Dc Voltage Rating: 28.0 volts Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
1.250 inches Dc Voltage Rating: 28.0 volts Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
Dc Voltage Rating: 28.0 volts Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
28.0 volts Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
Actuation Method: Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
Buoyancy Electrical Connection Type: Cable Internal Battery Accommodation: Not included
Electrical Connection Type: Cable Internal Battery Accommodation: Not included
Cable Internal Battery Accommodation: Not included
Internal Battery Accommodation: Not included
Not included
Current Rating At Maximum Rated Voltage:
500.0 milliamperes load
Float Quantity:
1
Operating Tempurature Rating:
Between -45.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Thread
Mounting Position:
Vertical
Contact Arrangement:
Spst, normally open
Relay:
Not included
Liquid Type For Which Designed:
Aircraft fuel
Aircraft Fuel For Which Designed:
Specific
Aircraft Fuel Grade Specificationification:
Mil-t-5624g
Aircraft Fuel Grade:
Grades jp-4, jp-5
Aircraft Fuel Grade Specificationific Gravity Rating:
0.845 at 15.6/15.6 degrees maximum spgr
Float Effective Travel:

Between 0.375 inches and 0.613 inches

NSN 5930-00-321-0255

Liquid Level Switch - Page 2 of 2



Mounting Dimensions:
An816-6d fitting
Tank Insertion Length:
2.812 inches
Fsc Application Data:
Aircraft fuel system
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T109-d

Mil-std (military Standard):

Mil-t-5624 spec.