

View Online at <https://aerobasegroup.com/nsn/5930-00-321-0343>

Hazardous Locations/environmental Protection:

Dustproof

First Flat Length:

0.688 inches single actuator

Flat Height:

0.182 inches single actuator and 0.192 inches single actuator

Shaft Diameter:

0.450 inches single actuator and 0.490 inches single actuator

Shaft Length:

0.906 inches single actuator

Overall Diameter:

1.359 inches

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Special Features:

Two no. 10-32 thd mtg holes spaced 1.594 in. C to c. Spring loaded automatic rotors from position x3 to position x2

Style Designator:

Circular wafer, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0