

View Online at <https://aerobasegroup.com/nsn/5930-00-321-0343>

**Hazardous Locations/environmental Protection:**

Dustproof

**First Flat Length:**

0.688 inches single actuator

**Flat Height:**

0.182 inches single actuator and 0.192 inches single actuator

**Shaft Diameter:**

0.450 inches single actuator and 0.490 inches single actuator

**Shaft Length:**

0.906 inches single actuator

**Overall Diameter:**

1.359 inches

**Individual Section Quantity:**

4

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

**Special Features:**

Two no. 10-32 thd mtg holes spaced 1.594 in. C to c. Spring loaded automatic rotors from position x3 to position x2

**Style Designator:**

Circular wafer, bushing mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A052b0