NSN 5930-00-321-0576

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-321-0576

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.690 inches

Overall Height:

3.409 inches

Overall Width:

1.830 inches

Case Material:

Metal

Actuator Style:

Nonadjustable arm

Actuator Width:

0.350 inches

Housing Height:

2.660 inches

Housing Length:

1.690 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.031 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.312 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 inch-ounces

Switch Actuating Force:

24.0 inch-ounces

Actuator Movement:

Between 30.0 pretravel degrees and 55.0 overtravel degrees and 15.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 connector, receptacle

NSN 5930-00-321-0576

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

