NSN 5930-00-321-0576

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-321-0576

Body Style:						
Hole mounted						
Hazardous Locations/environmental Protection:						
Dustproof						
Overall Length:						
1.690 inches						
Overall Height:						
3.409 inches						
Overall Width:						
1.830 inches						
Case Material:						
Metal						
Actuator Style:						
Nonadjustable arm						
Actuator Width:						
0.350 inches						
Housing Height:						
2.660 inches						
Housing Length:						
1.690 inches						
Housing Width:						
1.000 inches						
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:						
1.031 inches						
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:						
2.312 inches						
Maximum Voltage Rating In Volts:						
250.0 ac and 30.0 dc						
Inclosure Type:						
Fully enclosed						
Nonpile-up Contact Arrangement:						
1 pole, double throw, one position momentary single switch unit						
Switch Release Force:						
4.0 inch-ounces						
Switch Actuating Force:						
24.0 inch-ounces						
Actuator Movement:						
Between 30.0 pretravel degrees and 55.0 overtravel degrees and 15.0 differential degrees						
Contact Load Current Rating At Maximum Rated Voltage:						
10.000 amperes resistive dc and 10.000 amperes resistive ac						

Terminal Type And Quantity:

3 connector, receptacle

NSN 5930-00-321-0576

Sensitive Switch - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0