

View Online at <https://aerobasegroup.com/nsn/5930-00-321-6987>

**Thread Length:**

0.312 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Moisture resistant

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.205 inches single actuator and 0.215 inches single actuator

**Shaft Diameter:**

0.246 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.692 inches single actuator

**Individual Section Quantity:**

2

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

9 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Turret

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+8.000/+30.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Special Features:**

Printed wiring board with resistors and terminals attached to each section

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0