NSN 5930-00-322-2488

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-322-2488
Overall Length:
2.563 inches
Overall Height:
0.921 inches
Body Diameter:
1.181 inches
Body Height:
0.921 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Longest Horizontal Distance Between Mounting Centers:
2.188 inches
Shortest Horizontal Distance Between Mounting Centers:
1.094 inches
Longest Vertical Distance Between Mounting Centers:
2.188 inches
Shortest Vertical Distance Between Mounting Centers:
1.094 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit
Mounting Method:
Flange and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position diamond
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:

25.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

140.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Frequency In Hertz:

60.0 second voltage

NSN 5930-00-322-2488

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Precious Material:
Silver
Style Designator:
Disc w/flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0