NSN 5930-00-322-9666

Sensitive Switch - Page 1 of 2

Body Style:

4 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5930-00-322-9666

Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.520 inches
Overall Height:
0.844 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.113 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.312 inches
Actuator Length:
1.438 inches
Actuator Style:
Leaf
Actuator Width:
0.188 inches
Actuator Free Position Height:
0.344 inches
Maximum Voltage Rating In Volts:
125.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
10.0 ounces
Actuator Movement:
Between 0.045 pretravel inches and 0.018 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:

NSN 5930-00-322-9666

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0