## NSN 5930-00-323-1962

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-323-1962

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.938 inches
Overall Height:
0.875 inches
Overall Width:
0.562 inches
Individual Section Quantity:
1
Switch Contact Basic Design:
Pile-up
Pole Quantity:
4 single section front
Throw Quantity:
2 single section front
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob and cam actuated
Pile-up Contact Form Arrangement:
2c single switch single section in-line
Contact Voltage Rating In Volts:
110.0 ac at sea level
Rotor Through Connection Quantity:
1 single section
Cam Actuated Switch Contact Arrangement:
1 two circuit, double break/double make, both positions maintained single switch single section in-line
Switch Actuator Indexing Position Quantity:
3 single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section in-line
Contact Load Current Rating:
3.0 amperes resistive load ac at sea level
Style Designator:
In-line, pile-up, panel mount
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-00-323-1962

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0