## NSN 5930-00-323-2016

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-323-2016

**Thread Class:** 2a single mounting facility **Thread Length:** 0.375 inches single mounting facility **Overall Length:** 3.125 inches **Overall Height:** 2.375 inches **Overall Width:** 1.750 inches **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 11 single section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 6.0 lowest ac voltage rating at sea level **Switch Actuator Indexing Position Quantity:** 11 single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Switch Actuator Stop Device Type:** Adjustable stop single actuator **Contact Load Current Rating:** 1.0 amperes resistive load highest dc voltage rating at sea level **Style Designator:** Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

## NSN 5930-00-323-2016

Rotary Switch - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0