

View Online at <https://aerobasegroup.com/nsn/5930-00-324-1042>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.340 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

3.670 inches

**First Flat Length:**

0.560 inches 1st actuator

**Flat Height:**

0.215 inches 1st actuator

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

1.100 inches 2nd actuator

**Overall Diameter:**

1.150 inches

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Operating Temperature Range:**

-54.0/+71.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

8 each section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

195.0 degrees from nonturn device 1st actuator

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

8 1st actuator

**Shaft Type:**

Round, hollowed, flatted 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop 1st actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level and 100.0 milliamperes inductive load dc at sea level

**Special Features:**

Inter shaft 0.125 in. Diameter is push only for actuation of auxiliary switch

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0