NSN 5930-00-324-2978

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-324-2978

View Online at https://aerobasegroup.com/nsn/5930-00-324-2978
Thread Class:
3a single pressure connection
Inside Diameter:
0.125 inches single connection
Thread Length:
0.200 inches single pressure connection
Overall Length:
1.880 inches
Body Length:
1.340 inches
Overall Diameter:
1.310 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit
Mounting Method:
Clamp
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
27 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
25.00 pounds per square inch
Thread Size:
0.125 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Sensing Element Burst Pressure:
62.50 pounds per square inch
Terminal Type:
Wire hook
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
6.00 actuation point pounds per square inch gage and 5.50 deactuation point pounds per square inch gage and 0.50 differential point
pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

NSN 5930-00-324-2978

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0