NSN 5930-00-324-2978

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-324-2978

| View Online at https://aerobasegroup.com/nsn/5930-00-324-2978 |
|---|
| Thread Class: |
| 3a single pressure connection |
| Inside Diameter: |
| 0.125 inches single connection |
| Thread Length: |
| 0.200 inches single pressure connection |
| Overall Length: |
| 1.880 inches |
| Body Length: |
| 1.340 inches |
| Overall Diameter: |
| 1.310 inches |
| Pressure Switch Type: |
| Gage |
| Operating Tempurature Rating: |
| Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit |
| Mounting Method: |
| Clamp |
| Features Provided: |
| Electrical access port |
| Thready Qty Per Inch (tpi): |
| 27 single pressure connection |
| Contact Action Stimulus: |
| Increase |
| Proof Pressure: |
| 25.00 pounds per square inch |
| Thread Size: |
| 0.125 inches single pressure connection |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Sensing Element Burst Pressure: |
| 62.50 pounds per square inch |
| Terminal Type: |
| Wire hook |
| Contact Load Current Rating: |
| 5.0 amperes resistive load single voltage |
| Contact Adjustability: |
| Deactuation point not adjustable and actuation point not adjustable |
| Contact Stimulus Rating: |
| 6.00 actuation point pounds per square inch gage and 5.50 deactuation point pounds per square inch gage and 0.50 differential point |
| pounds per square inch gage |

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

NSN 5930-00-324-2978

Pressure Switch - Page 2 of 2



| Pressure Connector Type: |
|--|
| Plain, threaded internal single connection |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |
| Cylindrical |
| Thread Series Designator: |
| Npt single pressure connection |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A048b0