

View Online at <https://aerobasegroup.com/nsn/5930-00-324-3222>

Thread Class:

3a single pressure connection

Thread Length:

0.275 inches single pressure connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

Between 2.250 inches and 2.370 inches

Outside Diameter:

0.563 inches single connection

Body Length:

1.000 inches

Overall Diameter:

0.875 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 200.0 degrees fahrenheit

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

120.00 pounds per square inch

Thread Size:

0.5625 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

180.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

100.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

11.00 actuation point pounds per square inch gage and 7.00 deactuation point pounds per square inch gage and 3.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0