

View Online at <https://aerobasegroup.com/nsn/5930-00-325-8769>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

4.562 inches

**Overall Height:**

1.438 inches

**Overall Width:**

1.578 inches

**Body Length:**

3.562 inches

**Unthreaded Mounting Hole Diameter:**

0.221 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 1.080 inches and 1.084 inches

**Shortest Horizontal Distance Between Mounting Centers:**

Between 0.540 inches and 0.542 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 0.935 inches and 0.939 inches

**Temperature Sensing Element Type:**

Expanding shell

**Mounting Method:**

Flange and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage500.0 milliamperes resistive load third voltage2.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

-100.00/+650.00 actuation point degrees fahrenheit and -100.00/+650.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Voltage Rating In Volts:**

115.0 ac at sea level first voltage28.0 dc at sea level second voltage115.0 dc at sea level third voltage

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiq:**

A048b0