

View Online at <https://aerobasegroup.com/nsn/5930-00-325-8769>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

4.562 inches

Overall Height:

1.438 inches

Overall Width:

1.578 inches

Body Length:

3.562 inches

Unthreaded Mounting Hole Diameter:

0.221 inches

Longest Horizontal Distance Between Mounting Centers:

Between 1.080 inches and 1.084 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.540 inches and 0.542 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.935 inches and 0.939 inches

Temperature Sensing Element Type:

Expanding shell

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage500.0 milliamperes resistive load third voltage2.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

-100.00/+650.00 actuation point degrees fahrenheit and -100.00/+650.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage28.0 dc at sea level second voltage115.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0