

View Online at <https://aerobasegroup.com/nsn/5930-00-326-1533>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

6.312 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Shaft Length:

1.312 inches single actuator

Individual Section Quantity:

9

Longest Horizontal Distance Between Mounting Centers:

2.296 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.296 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

3 each section rear

Mounting Facility Circle Radius:

0.906 inches 2nd mounting facility

Mounting Method:

Bracket single mounting facility and threaded stud single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0