## NSN 5930-00-327-7223

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-327-7223

**Thread Class:** 

2a single pressure connection

**Overall Length:** 

4.750 inches

**Overall Diameter:** 

4.219 inches

**Unthreaded Mounting Hole Diameter:** 

0.625 inches

**Pressure Switch Type:** 

Gage

**Operating Tempurature Rating:** 

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:** 

Clamp and unthreaded hole

**Features Provided:** 

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

**Contact Action Stimulus:** 

Increase

Thread Size:

0.625 inches single pressure connection

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Connector, receptacle

**Contact Load Current Rating:** 

2.0 amperes resistive load single voltage

**Contact Adjustability:** 

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:** 

+7.60/+8.40 actuation point inches of water and +6.20/+6.80 deactuation point inches of water

**Contact Adjustment Type:** 

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level single voltage

**Pressure Connector Type:** 

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

**Style Designator:** 

Cylindrical

## NSN 5930-00-327-7223

Pressure Switch - Page 2 of 2



|  | T | hr | ead | <b>Series</b> | Design | nator |
|--|---|----|-----|---------------|--------|-------|
|--|---|----|-----|---------------|--------|-------|

Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0