NSN 5930-00-327-7225

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-327-7225

Overall Width:
2.500 inches
Body Diameter:
2.500 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
1.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Flange and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Threaded stud
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
5.00 actuation point pounds per square inch and 4.00 deactuation point pounds per square inch and 1.00 differential point pounds per
square inch
Contact Voltage Rating In Volts:
24.0 dc at sea level single voltage
Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas
Style Designator:
Cylindrical w/mounting lugs
Thread Series Designator:
Not single pressure connection

N/a

Shelf Life:

NSN 5930-00-327-7225

Pressure Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A048b0