

View Online at <https://aerobasegroup.com/nsn/5930-00-327-7238>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.125 inches

Body Diameter:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Mounting Facility Centers:

2.375 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Automatic reset

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

250.00 pounds per square inch gage

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

150.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

13.00 actuation point pounds per square inch gage and 11.00 deactuation point pounds per square inch and 2.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0