

View Online at <https://aerobasegroup.com/nsn/5930-00-327-7238>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.125 inches

**Body Diameter:**

2.500 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Mounting Facility Centers:**

2.375 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Automatic reset

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

250.00 pounds per square inch gage

**Thread Size:**

0.125 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

150.00 pounds per square inch gage

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

13.00 actuation point pounds per square inch gage and 11.00 deactuation point pounds per square inch and 2.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

480.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0