

View Online at <https://aerobasegroup.com/nsn/5930-00-327-7263>

Thread Class:

3a single pressure connection

Thread Length:

0.812 inches single pressure connection

Overall Length:

4.500 inches

Overall Width:

3.625 inches

Body Diameter:

3.000 inches

Body Length:

2.781 inches

Unthreaded Mounting Hole Diameter:

Between 0.195 inches and 0.200 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Absolute

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.50/+200.00 actuation point pounds per square inch and +0.50/+200.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

2.50 differential point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0