

View Online at <https://aerobasegroup.com/nsn/5930-00-327-7263>

**Thread Class:**

3a single pressure connection

**Thread Length:**

0.812 inches single pressure connection

**Overall Length:**

4.500 inches

**Overall Width:**

3.625 inches

**Body Diameter:**

3.000 inches

**Body Length:**

2.781 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.195 inches and 0.200 inches

**Distance Between Mounting Facility Centers:**

3.000 inches

**Pressure Switch Type:**

Absolute

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.4375 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

3.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+0.50/+200.00 actuation point pounds per square inch and +0.50/+200.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

2.50 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

30.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0