

View Online at <https://aerobasegroup.com/nsn/5930-00-327-7269>

**Thread Class:**

3a single pressure connection

**Inside Diameter:**

0.125 inches single connection

**Overall Length:**

4.016 inches

**Overall Width:**

4.016 inches

**Body Diameter:**

3.000 inches

**Body Length:**

Between 2.750 inches and 2.812 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.227 inches and 0.232 inches

**Longest Horizontal Distance Between Mounting Centers:**

Between 0.890 inches and 0.910 inches

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

75.00 pounds per square inch

**Thread Size:**

0.125 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

500.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

19.00 actuation point pounds per square inch and 17.50 deactuation point pounds per square inch and 0.50 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

30.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0