

View Online at <https://aerobasegroup.com/nsn/5930-00-327-7788>

Thread Class:

2a single mounting facility

Thread Length:

0.360 inches single mounting facility and 0.400 inches single mounting facility

Overall Length:

Between 1.170 inches and 1.270 inches

Shaft Diameter:

0.240 inches single actuator and 0.260 inches single actuator

Shaft Length:

0.730 inches single actuator and 0.770 inches single actuator

Overall Diameter:

Between 1.000 inches and 1.060 inches

Nonturn Device Radius:

0.140 inches at 7: 30 o'clock and 0.160 inches at 7: 30 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 7: 30 o'clock

Operating Temperature Range:

-65.0/+200.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

5 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0